



DIMENSIONI - DIMENSIONS

| | | | | | | | | | | | | ISO CONNECTION | | | | | |
|-----|----|----|-------|----|----|---|------|------|-----|-------|----|----------------|-------|-----|--------|------|----------|
| A | B | ØC | D | E | F | G | H | ØI | L | L1 | M | ØJ | K | ØW | X | DSQP | ISO 5211 |
| 145 | 73 | 28 | 168,5 | 45 | 30 | 3 | 98,5 | 56,5 | 367 | 175,5 | 20 | 70 | M8X12 | 102 | M10X15 | 22 | F07/F10 |

| CONSUMI D'ARIA AIR CONSUMPTION | | |
|-----------------------------------|------|------|
| DE | N Lt | 4,40 |
| RM | N Lt | 1,85 |

| PESO WEIGHT | | |
|----------------|----|-------|
| DE | Kg | 10,65 |
| RM | Kg | 13,21 |

| MOMENTI TORCENTI PER ATTUATORI A DOPPIO EFFETTO IN NM DOUBLE ACTING ACTUATORS TORQUE CHART IN NM | | | | | | | | | | |
|---|-------|-------|-------|----------|-------|-------|-------|-------|--------|--|
| 2 Bar | 3 Bar | 4 Bar | 5 Bar | 5,62 Bar | 6 Bar | 7 Bar | 8 Bar | 9 Bar | 10 Bar | |
| 125,8 | 188,7 | 251,6 | 314,5 | 352,7 | 377,4 | 440,3 | 503,2 | 566,1 | 629,0 | |

MOMENTI TORCENTI PER ATTUATORI A SEMPLICE EFFETTO IN NM - SPRING RETURN ACTUATOR TORQUE CHART IN NM

| COPPIA DI APERTURA - POS 2 OPENING TORQUE | | | | | | | | | | | | | | | | | |
|---|--|-------|-------|-----|-------|-----|-------|------|----------|-------|-------|-------|-------|-------|-------|-------|--|
| N° MOLLE SPRINGS | POS. 1 - COPPIA DELLE MOLLE POS. 1 - SPRINGS TORQUE | | 3 Bar | | 4 Bar | | 5 Bar | | 5,62 Bar | | 6 Bar | | 7 Bar | | 8 Bar | | |
| | START | END | START | END | START | END | START | END | START | END | START | END | START | END | START | END | |
| 5+5 | 251,0 | 157,8 | - | - | - | - | 156,7 | 63,5 | 194,9 | 101,7 | 219,6 | 126,4 | 282,5 | 189,3 | 345,4 | 252,2 | |