



DIMENSIONI - DIMENSIONS

| | | | | | | | | | | | | ISO CONNECTION | | | | | |
|-----|----|----|-----|----|----|---|-------|------|-------|-------|----|----------------|--------|-----|--------|-------|----------|
| A | B | ØC | D | E | F | G | H | ØI | L | L1 | M | ØJ | K | ØW | X | DSQ P | ISO 5211 |
| 181 | 91 | 28 | 202 | 45 | 31 | 3 | 124,5 | 54,5 | 380,5 | 180,5 | 20 | 102 | M10X15 | 125 | M12X18 | 27 | F10/F12 |

| CONSUMI D'ARIA AIR CONSUMPTION | | |
|-----------------------------------|------|------|
| DE | N Lt | 4,60 |
| RM | N Lt | 2,50 |

| PESO WEIGHT | | |
|----------------|----|-------|
| DE | Kg | 16,20 |
| RM | Kg | 21,00 |

| MOMENTI TORCENTI PER ATTUATORI A DOPPIO EFFETTO IN NM DOUBLE ACTING ACTUATORS TORQUE CHART IN NM | | | | | | | | | | |
|---|-------|-------|-------|----------|-------|-------|-------|-------|--------|--|
| 2 Bar | 3 Bar | 4 Bar | 5 Bar | 5,62 Bar | 6 Bar | 7 Bar | 8 Bar | 9 Bar | 10 Bar | |
| 181,2 | 271,8 | 362,4 | 453,0 | 509,2 | 543,6 | 634,2 | 724,8 | 815,4 | 906,0 | |

MOMENTI TORCENTI PER ATTUATORI A SEMPLICE EFFETTO IN NM - SPRING RETURN ACTUATOR TORQUE CHART IN NM

| COPPIA DI APERTURA - POS 2 OPENING TORQUE | | | | | | | | | | | | | | | | | |
|---|--|-------|-------|-----|-------|------|-------|-------|----------|-------|-------|-------|-------|-------|-------|-------|--|
| N° MOLLE SPRINGS | POS. 1 - COPPIA DELLE MOLLE POS. 1 - SPRINGS TORQUE | | 3 Bar | | 4 Bar | | 5 Bar | | 5,62 Bar | | 6 Bar | | 7 Bar | | 8 Bar | | |
| | START | END | START | END | START | END | START | END | START | END | START | END | START | END | START | END | |
| 5+5 | 310,8 | 245,3 | - | - | 117,1 | 51,6 | 207,7 | 142,2 | 263,9 | 198,4 | 298,3 | 232,8 | 388,9 | 323,4 | 479,5 | 414,0 | |