



DIMENSIONI - DIMENSIONS												ISO CONNECTION					
A	B	ØC	D	E	F	G	H	ØI	L	L1	M	ØJ	K	ØW	X	DSQ P	ISO 5211
131	66	19,5	154	45	30	3	95,5	40,5	261	123	14	70	M8X12	102	M10X15	22	F07/F10

CONSUMI D'ARIA AIR CONSUMPTION		
DE	N Lt	2,45
RM	N Lt	1,20

PESO WEIGHT		
DE	Kg	6,45
RM	Kg	7,89

MOMENTI TORCENTI PER ATTUATORI A DOPPIO EFFETTO IN NM DOUBLE ACTING ACTUATORS TORQUE CHART IN NM									
2 Bar	3 Bar	4 Bar	5 Bar	5,62 Bar	6 Bar	7 Bar	8 Bar	9 Bar	10 Bar
64,4	96,6	128,8	161,1	180,4	193,3	225,5	257,7	289,9	322,1

MOMENTI TORCENTI PER ATTUATORI A SEMPLICE EFFETTO IN NM - SPRING RETURN ACTUATOR TORQUE CHART IN NM																	
COPPIA DI APERTURA - POS 2 OPENING TORQUE																	
N° MOLLE SPRINGS	POS. 1 - COPPIA DELLE MOLLE POS. 1 - SPRINGS TORQUE		3 Bar		4 Bar		5 Bar		5,62 Bar		6 Bar		7 Bar		8 Bar		
	START	END	START	END	START	END	START	END	START	END	START	END	START	END	START	END	
5+5	116,2	86,6	-	-	42,2	12,6	74,5	44,9	93,8	64,2	106,7	77,1	138,9	109,3	171,1	141,4	